



Covrex® and its partners would like to thank you for the purchase of your new pool cover.

We hope you will enjoy it for years to come, and we are convinced it will help you insulate, and maintain your swimming pool.

#### To operate the cover:

Turn and release the key switch in the direction you want the cover to move- Do not hold the key switch for more than a couple of seconds as this will initiate "manual mode" and the cover will stop when the key switch is released (this is ideal for maintenance /cleaning of the cover)

The remote control (were fitted) will also work in the same way.

#### Programming:

In the event of the cover losing its open and closed position (e.g. due to an electricity shortage/spike) it can easily be reprogrammed by following these steps:

1. Switch off the control panel with the red power button located on the bottom for ten seconds and the turn back on and wait until "Ready" appears on the display.
2. Press the red programming button for three seconds until the word "**Programming**" appears on the display. The red LED control lamp next to the programming button will be flashing.
3. Now activate the external key switch and bring the cover into the Start/open position (in the pit). During this opening operation the red LED lamp near the **white open button** is flashing all the time.  
**Note- If it is a pool bottom system, do not let the end of the cover go below the gap at pool floor level, it is recommended that two slat sections are left visible.**
4. If required you can adjust the position of the cover by rolling it in and out. The motor must run for at least 4 seconds in any direction.
5. Switch off the red power button of the control box.
6. Switch on the red power button of the control box.
7. Press the red programming button for three seconds until the word "**Programming**" appears on the display. The red LED control lamp next to the programming button will be flashing.

8. Now activate the external key switch and bring the cover into the Stop/Closed position (fully on the pool). During this closing operation the red LED lamp next to the **white close button 3** is flashing all the time.

9. Operate the cover until the pool is closed.

10. Press the red programming button for a second. . -> **“Position 1”** appears on the display, the LED is flashing slowly. Press the red button again.. -> **“Position 2”** appears. Press the red button for a third time..> **“Text Saved”** will appear and the red led will go off.

**The cover will automatically remember the open position**

**The cover is now programmed!!**

Note - the **“Text saved”** will remain until the cover is next operated.

In case of problems please contact your pool installer.